



# JINAN HONGYANG CNC MACHINERY CO., LTD

## Huajiang 2.2KW ( $\Phi$ 85\*230 ) Water-cooled Spindle Motor for Woodworking Advertisements

 	<b>model:</b>	85 2.2KW ER20
	<b>Dimensions:</b>	$\Phi$ 85*230 $\Phi$ m/m
	<b>Rotating speed:</b>	24000RPM
	<b>power:</b>	2.2KW
	<b>Voltage:</b>	220V/380V
	<b>frequency:</b>	400HZ
	<b>Bearing:</b>	Four bearings
	<b>cooling method:</b>	Water cooling
	<b>Chuck nut:</b>	ER20
	<b>Current:</b>	/

1. Huajiang 2.2kw ( $\phi$ 85\*230 ) water-cooled spindle motor for woodworking advertisements should be used with the inverter. The specifications and parameters of the inverter should match the parameters of the [water cooled spindle motor](#). If the settings are incorrect, the spindle motor will be burned.
2. Before using, the water-cooled spindle motor must ensure that the cooling circulation system is working normally, and it is strictly prohibited to use it without cooling water.
3. During the storage and transportation of the spindle motor, the state of the high-speed grease inside the bearing will change, and the customer should run the spindle at a low speed before use.